



## SWELDex profi, mobile, 2 arms

This mobile welding smoke filter is suitable for industrial use. The unit is equipped with two exhaust arms in various lengths, a preliminary filter and a main filter (two stage filtration) with

a separating efficiency of  $\geq 99.9\%$ .

Automatic filter monitoring indicates, when a filter needs to be changed. This unit offers the possibility to

exhaust welding smoke at two workplaces close to each other at the same time.

### Accessories:

The units can also be equipped with workstation lights in the fume hood, and on/off switch on the fume hood, and automatic start-stop.

Technical data	
Ventilator capacity	2.200 m <sup>3</sup> /h
Suction capacity	2 x 700 m <sup>3</sup> /h
Motor capacity	1,1 kW
Connection voltage	3 x 400 V / 50 Hz
Separating efficiency	$\geq 99,9\%$
Noise level	approx. 68 dB (A)
Weight (without arm)	95 kg
Dimension (L x W x H)	655 x 655 x 1.020 mm

Dimension  
(L x W x H):  
655 x 655 x 1.020 mm



Model	Weight w/o arm	Article no.	Price €/pc.
400 V, 50 Hz, ventilator 2.200 m <sup>3</sup> /h, motor 1.1 kW, exhaust arm 2 m, Ø 150 mm	95 kg	ABS-PROFI-2-2	
400 V, 50 Hz, ventilator 2.200 m <sup>3</sup> /h, motor 1.1 kW, exhaust arm 3 m, Ø 150 mm	95 kg	ABS-PROFI-2-3	
400 V, 50 Hz, ventilator 2.200 m <sup>3</sup> /h, motor 1.1 kW, exhaust arm 4 m, Ø 150 mm	95 kg	ABS-PROFI-2-4	

Delivery approx. 2-3 weeks