

Hitsauskaapeli, kuparia, öljyn ja kemikaalien kestävä

Eriste: PVC-seos

Väri: Musta

Merkintä: ARFLEX/SIMPLEX **mm²CE

Murtolujuus: 15,8 N/mm²

10- 50 mm²

50m/100m /kieppi

70-120 mm²

50m /kieppi



Til.no	mm ²	max.johdon vastus 20 ⁰	lankojen Ømm	max ulkoØ	eristeen vahvuus	kaapelin paino	Virransieto (Virtakapas.)		
							Onm/km	100%	60%
137010	10	1,910	0,31	7,00	1,60	0,120	85	110	160
137016	16	1,210	0,31	8,00	1,80	0,180	125	175	235
137025	25	0,780	0,31	10,00	2,00	0,270	170	230	320
137035	35	0,554	0,31	12,00	2,20	0,370	215	290	400
137050	50	0,386	0,31	13,50	2,40	0,510	275	365	510
137070	70	0,272	0,31	16,00	2,60	0,710	345	460	640
137095	95	0,206	0,31	18,50	2,80	0,940	420	560	780
137120	120	0,161	0,31	20,50	3,00	1,190	490	650	900

KONELIITTIMET

132012	K 25	Amp. 60%:200 / 16-25 mm ²
132015	K 50	Amp. 60%:300 / 35-50 mm ²
132017	K 70	Amp. 60%:500 / 70-95 mm ²
132025	N 25	Amp. 60%:200 / 16-25 mm ²
132050	N 50	Amp. 60%:300 / 35-50 mm ²
132070	N 70	Amp. 60%:500 / 70-95 mm ²



KAAPELILIITTIMET

132125	K 25	Amp. 60%:200 / 10-25 mm ²
132150	K 50	Amp. 60%:300 / 35-50 mm ²
132170	K 70	Amp. 60%:400 / 50-70 mm ²
132190	K 95	Amp. 60%:400 / 70-95 mm ² /2:lla ruuvilla
132225	N 25	Amp. 60%:200 / 10-25 mm ²
132250	N 50	Amp. 60%:300 / 35-50 mm ²
132270	N 70	Amp. 60%:400 / 50-70 mm ²
132290	N 95	Amp. 60%:400 / 70-95 mm ² /2:lla ruuvilla




K25 tappi Ø 9mm
K50-70-90 " Ø13mm



HAAROITUSLIITIN

132370 KAB 70-95 2xN,1xK /max virta 500A



**MYÖS VALMIITA
KAAPELISARJOJA
KYSY !**

KAAPELIKENGÄT

138216	16mm ²	Ø 10mm
138225	25mm ²	Ø 10mm
138235	35mm ²	Ø 14mm
138250	50mm ²	Ø 14mm
138280	75mm ²	Ø 16mm

