

K 225



NEW 250



NEW 250 DV



TRS 30



TEKNISET TIEDOT		PYÖRÖSAHAT													
		K225		NEW250		TRS275		NEW300		NEW315		NEW350		PUOLIAUTOMAATTI NEW350S	
Tiluskoodi		151225		15250		151275		151300		151315		151350		151355	
Liitäntäjännite	V	230V / 1 v.		400V / 3 v.		400V / 3 v.		400V / 3 v.		400V / 3 v.		400V / 3 v.		400V / 3 v.	
Moottori	kW	0,75		0,95-1,32		1,1-1,5		1,5-2,2		1,5-2,2		1,8-2,4		1,8-2,4	
Terän kierrosnop.	rpm	52		52-104		40-80		40-80		40-80		40-80		40-80	
Ruuvipenkin avauma	mm	70		100		105		190		190		190		120	
Leikkuupää kääntyy	aste	45° vasen		45° vas/oik		45° vas/oik		45° vas/oik		45° vas		45° vas		45° vas - 45° oik	
Leikkuutehot	aste	90°	45°vas	90°	45°	90°	45°	90°	45°	90°	45°vas.	90°	45°vas	90°	45°vas.
Leikkaa umpi Ø	mm	30	30	40	35	45	40	55	50	65	60	60	55	60	55
putki Ø	mm	65	60	70	65	80	80	100	90	100	90	110	90	110	80
neliö	mm	55x55	50x50	70x70	60x60	80x80	70x70	90x90	80x80	90x90	80x80	100x100	85x85	100x100	80x80
suorakaide	mm	45x75	40x60	55x65	90x130	100x70	80x70	140x70	70x85	140x70	70x85	155x80	90x85	80x120	80x80
Terä	Ømm	225		250		275		315		315		350		350	
Paino	kg	41		91		98		160		176		204		280	

**NEW
300**



**NEW
315**



**NEW
350**



**NEW
350 S**

