

NTM 315



NTM 350



NTS 315



NTS 350



NTA 350



NTM 350 S



NTA 315



TEKNISET TIEDOT

PYSTYJOHDESAHAT

MANUAALIT

PUOLIAUTOMAATIT

AUTOMAATIT

		NTM 315		NTM 350		NTS 315		NTM 350 S		NTS 350		NTA 315		NTA 350	
		90°	45° oik.	45° vas.	60° vas.	90°	45° oik.	45° vas.	60° vas.	90°	45° oik.	45° vas.	60° vas.	90°	45° oik.
Tilaukoodi		153315		153350		153316		153355		153351		153320		153352	
Litäntäjännite	V	400V / 3 v.		400V / 3 v.		400V / 3 v.		400V / 3 v.		400V / 3 v.		400V / 3 v.		400V / 3 v.	
Moottori	kW	1,3-1,8		1,9-2,5		1,3-1,8		1,9-2,5		1,9-2,5		1,3-1,8		1,9-2,5	
Terän kierrosnop.	rpm	33-66		36-72		33-66		36-72		25-50		33-66		25-50	
Ruuvipenkin avaus	mm	160		185		160		185		185		120		185	
Leikkuupää kääntyy	aste	90°	45° oik.	45° vas.	60° vas.	90°	45° oik.	45° vas.	60° vas.	90°	45° oik.	45° vas.	90°	45° oik.	45° vas.
Leikkaa umpi Ø	mm	70	70	70	70	100	100	100	90	100	100	100	70	70	70
putki Ø	mm	100	100	100	80	120	120	120	90	100	100	100	100	90	90
neliö	mm	90	90	90	70	100	90	90	90	90	90	90	100	80	80
suorakaide	mm	80x135	80x100	80x100	70x70	90x170	90x125	90x125	90x90	80x135	80x100	80x100	70x70	90x170	90x130
Terä	Ømm	315		350		315		350		350		315		350	
Paino	kg	270		450		300		480		500		550		900	