



High power MIG-MAG/FLUX/MMA/TIG multi-process inverter generator suitable for heavy duty use on worksites and industrial environments. MIG-MAG/TIG welding of all types of steels and steel by-products and MMA welding of all types of electrodes up to 8 mm in diameter. The optional removable wire feeder and connection cables make it possible to increase the field of intervention. Compactness and easy transport features guarantee high levels of mobility and flexibility of use. Complete with wirefeeder, MIG-MAG welding accessories, trolley and water cooling unit GRA 3000.



**INDUSTRIAL**



**Norms:**

CODE	V <sub>ph</sub> V 50/60Hz	A <sub>MIN</sub> A	A <sub>MAX</sub> 40°C EN60974-1	A <sub>60%</sub> 40°C EN60974-1	V <sub>o</sub> V	A <sub>60%</sub> I <sub>MAX</sub> A	P <sub>60%</sub> MAX kW	η n%	cosφ
816044	400 3 ph	10 600 DC	500 40 % DC	400 DC	73	20 35	13 23	86	0,9
ST mm	SS mm	AL mm	FX mm	BZ mm	Ø <sub>E</sub> MIN MAX DC mm	IP	W <sub>L</sub> H L cm(L,W,H)	kg	BAR CODE
0,6 2,4	0,8 2,4	0,8 1,6	1 2,4	0,8 1,2	1,6 8	IP23	95 45 145	108	8004897948 39 3