

Intelligent battery charger with electronic control of the charging current, and automatic interruption and restart (PULSE-TRONIC). Automatic charge (PULSE-TRONIC) and rapid charge (BOOST), of all maintenance free, sealed batteries (GEL/AGM/START-STOP), and free electrolyte batteries (WET) with 12/24V voltages of motorcycles, cars, vans, tractors and boats. Characteristics: 3 charge current levels for each voltage \* warning led for charging status, end of charge, thermostatic interruption due to short circuit of output cables or polarity reversal \* supplied with three different charging cables.



**Pulse Tronic**



**AUTOMOTIVE**

**CONSUMER**



<p><b>AUTOMATIC CONTROL OF THE CHARGE LEVEL</b></p>	<p><b>CHARGING STATUS WARNING LED</b></p>	<p><b>WIDE RANGE OF USE</b></p>	<p><b>SHORT-CIRCUIT, POLARITY REVERSAL PROTEC.</b></p>	<p><b>3 DIFFERENT TYPES OF CHARGING CABLES</b></p>

Norms:		LVD: EN 60335-2-29	EMC: EN 55014-1,2;	EMC: EN 61000-3-2,3					
CODE	V <sub>ph</sub>	P	V	A <sub>EFF</sub>	A <sub>EN</sub>	C <sub>MIN/MAX</sub>	☀	W <sub>L</sub>	kg
807563	230 1 ph	110	12 24	8 4	8 4	5 180	3	30 9,5 5,5	1,3
BAR CODE	☐								
8004897808 00 0	pz/pallet 180								