

Intelligent battery charger with electronic control of the charging current, and automatic interruption and restart (PULSE-TRONIC). Normal charge (CHARGE), automatic charge (PULSE-TRONIC) and rapid charge (BOOST), of all maintenance free, sealed batteries (GEL/AGM/START-STOP), and free electrolyte batteries (WET) with 12V voltages of motorcycles, cars, vans, tractors and boats. The CHARGE mode is advisable when the type of battery to be charged is unknown, the PULSE-TRONIC (GEL/AGM or WET) mode allows the automatic control of the battery status. Characteristics: 3 charge current levels * warning led for charging status, end of charge, thermostatic interruption due to short circuit of output cables or polarity reversal * supplied with three different charging cables.



Pulse Tronic



AUTOMOTIVE

CONSUMER



AUTOMATIC CONTROL OF THE CHARGE LEVEL	CHARGING STATUS WARNING LED	WIDE RANGE OF USE	SHORT-CIRCUIT, POLARITY REVERSAL PROTEC.	3 DIFFERENT TYPES OF CHARGING CABLES

Norms: LVD: EN 60335-2-29 EMC: EN 55014-1,2; EMC: EN 61000-3-2,3

CODE	V _{ph} V50/60Hz	P W	+ - V	A _{EFF} A	A _{EN} A	C MIN/MAX Ah15h		W L H cm(L,W,H)	kg
807562	230 1 ph	220	12	16	16	10 250	3	30 9,5 5,5	1,4
BAR CODE									
8004897738 61 1	pz/pallet 180								